

Kingston™ Comfort Height®

Elongated toilet bowl K-25076-SS

Features

- Ideal for commercial installations.
- Antimicrobial finish inhibits the growth of mold-, mildew-, stainand odor-causing bacteria on the fixture surface.
- Elongated bowl offers added room and comfort.
- Comfort Height® feature offers chair-height ADA-compliant seating.
- 2-1/8" fully glazed trapway.
- Combines with a K-25100, K-25100-RA, K-25100-T or K-25100-TR tank to create a complete K-25077-SS, K-25077-SSRA, K-25077-SST or K-25077-SSTR Kingston two-piece toilet.

Installation

- Three-bolt quick-connect installation.
- Standard 12" rough-in.
- Seat not included.

Included Components

Additional Components: Hardware accessory pack



ADA CSA B651 OBC

Codes/Standards
ASME A112.19.2/CSA B45.1
ADA
ICC/ANSI A117.1
CSA B651
OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White





Kingston™ Comfort Height®

Elongated toilet bowl K-25076-SS

No image available. This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor
Bowl shape: Elongated

Flush type: Gravity siphon jet Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.28 gpf (4.8 lpf)

Water surface size: 10-5/8" x 6-15/16" (269 mm x 176 mm)

Rim to water surface: 5-5/8" (143 mm) Rough-in: 12" (305 mm)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations. Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

